

Dual Relay Modules

AS6052-00

Low Voltage

AS6053-00

Low Voltage w/Isolator

AS6054-00

High Voltage

AS6055-00

High Voltage w/Isolator



Back side of an AS6053



Back side of an AS6052

Standard Features

- Provides two independently configurable Form C contacts per address
- Contacts are rated as follow:
AS6052/ AS6053: 2A @ 30 VDC / 0.5A @ 120 VAC
AS6054/ AS6055: 8A @ 30VDC / 4.8A @ 250 VAC
- Up to 127 devices can be used on each SLC loop
- Visible Bi-colored LED is software controlled and can be programmed to blink red or green when polled. The LED can be latched on when activated. (For All Models)
- Yellow LED indicates a short circuit condition (AS6053 & AS6055 only)
- Programming is highly flexible providing 16 priority states plus zoning capability
- Operates on Class A or Class B SLC loop

Operation

The Dual Relay Modules have been designed to provide flexible and quick response to emergency conditions. The Avenger Systems Series allows independent control of two form C contacts for a variety of normally open and normally closed contact applications such as fan operation, elevator recall, door closure, and auxiliary notification.

Each Avenger Systems Series module provides independent control of two Form C contacts while utilizing one SLC (Signaling Line Circuit) address. The modules have a highly configurable programming algorithm that allows the user to set up groups of devices (zoning) for simultaneous operation of multiple AS6052, AS6053, AS6054, AS6055 modules. The operating parameters are maintained by the module and do not require individual communication with the control panel during the emergency condition to operate. The control panel broadcasts the control command on the SLC loop and the Avenger Systems Series modules do the rest based on their custom configuration. Since mechanically latching relays are used within the Avenger Systems Series modules, a separate 24VDC power source is not required.



This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

For more information, contact Avenger. Phone: 800.270.3066

